

SUBFIELD 7 – SCRIPT OF THE BASE ACCESS POINT

This subfield identifies the scripts of the base access point. It is used when within the COBISS system we create access points in other scripts alongside the access points in the script of cataloguing.

The subfield may be used in 2XX, 4XX, 5XX and 7XX fields. In systems in which they create parallel authorized access points in Cyrillic and Latin scripts the use of subfield 7 is mandatory in the parallel 2XX fields.

For more detailed instruction see chapter *Introduction, Guidelines for Use*.

EXAMPLES

1. *

100	□□	ba cslv gba
200	□1	a Papamárkos b Dimosthénis
400	□1	7ga 9gre a Παπαμάρκος b Δημοσθένης

2. * COBISS.net

100	□□	ba cbul gca
200	□1	7ca a Соловьев b Владимир Сергеевич f 1853-1900
200	□1	7ba a Solov'ev b Vladimir Sergeevic f 1853-1900
400	□1	7ca a Соловьев b Владимир f 1853-1900
700	□□	31324645 7ca 9bul a Соловьев b Владимир Сергеевич f 1853-1900 (In fields 200 the access points are entered in both Cyrillic and Latin script, and in fields 400 and 700 the access points are entered in Cyrillic script.)

3. * COBISS.net

100	□□	ba cbul gca
200	□1	7ca a Кинг b Стивън f 1946-
200	□1	7ba a King b Stephen f 1946-
400	□1	5e 7ca a Бакман b Ричард
400	□1	5e 7ba a Bachman b Richard (Both access points – the authorized and the variant access point – are entered in Cyrillic and Latin script.)

4. * COBISS.net

100	□□	ba csrp gcb
200	□1	7ca a Толстой b Лев Николаевич f 1828-1910
200	□1	7ba a Tolstoj b Lev Nikolaevič f 1828-1910
400	□1	7cb 9srp a Толстој b Лав Николајевич f 1828-1910
400	□1	7ba 9srp a Tolstoj b Lav Nikolajevič f 1828-1910

5. * COBISS.net

100	□□	ba csrp gcb
200	□1	7cb a Дибрей b Жан-Луи f 1914-1995
200	□1	7ba a Dubreuil b Jean-Louis f 1914-1995
500	□1	3<nnn> 5e 7cb 9srp a Кампањ b Клод
500	□1	3<nnn> 5e 7ba 9fre a Campagne b Claude